

Aktive Differential-Tastköpfe | Active Differential Probes

Übersicht | Overview

Type	Order No.	Attenuation Ratio	Bandwidth	Max. Input Voltage (DC + Peak AC)			Vrms	Accuracy
				Differential Mode	Common Mode	absolute Maximum	absolute Maximum	
TT-SI 9001	15101	x10 x100	25 MHz	±70V ±700V	±700V ±700V	±1400V ±1400V	100Vrms CAT III	±2 %
TT-SI 9002	15102	x20 x200	25 MHz	±140V ±1400V	±1400V ±1400V	±1400V ±1400V	1000Vrms CAT III	±2 %
TT-SI 9101	15111	x10 x100	100 MHz	±70V ±700V	±700V ±700V	±1400V ±1400V	1000Vrms CAT III	±2 %
TT-SI 9110	15120	x100 x1000	100 MHz	±140V ±1400V	±1400V ±1400V	±1400V ±1400V	1000Vrms CAT III	±2 %
TT-SI 9010	15106	x100 x1000	70 MHz	±700V ±7000V	±7000V ±7000V	±7000V ±7000V	2500Vrms CAT I	±2 %
TT-SI 9010A	15108	x100 x1000	70 MHz	±700V ±7000V	±7000V ±7000V	±7000V ±7000V	5000 Vrms CAT I	±2 %
TT-SI 50	15130	x10	50 MHz	±70V	±700V	±700V	600Vrms CAT I	±1 %
TT-SI 51	15131	x100	50 MHz	±700V	±1400V	±1400V	600Vrms CAT II	±1 %
TT-SI 200	15138	x10	200 MHz	±20V	±60V	±60V	60Vrms CAT I	±1 %