

info@kelvin-

## INNOLOG DRYICE TEMPERATURE DATA LOGGER



## Data Sheet

Sensor type	internal RTD
Temperature unit :	°C or °F
operating range:	- 80°C to +65°C
Accuracy:	0.5°C from -20°C to +40°C +/- 1°C from -80°C to -20°C and from +40°C to +65°C
Resolution:	0.1°C/F
Time reference :	UTC+00
Storage capacity:	16.000 memory points
Standard recording interval:	5mn - factory adjustable
Standard start delay:	0 mn - factory adjustable
Maximum run time :	30 days
Maximum storage duration before use :	16 months
Start/Stop mode :	Push Start/Stop button - Automatic stop when connected to computer
	$OK(\sqrt)$ , Alarm $(*)$ , device status (ready, start delay, recording, stop)
	Temperature statistics (current/max/min/avg/mkt)
	Duration time has been recorded
	Mark records
LCD Display	Battery power
Reporting:	Automatic generation of PDF and CSV reports - certification of validation in memory
computer interface:	USB 2.0
Size:	106*51*18mm
Weight:	18g
Standard Alarms :	single event, up to 2 alarms
Certifications:	CE、RoHS、DO160、IATA PI970 II
IP rating :	IP 64

Innolog Data Sheet VER 1.0.0 01/23 signed by: P.POULET